

<b>M390 QUATRO regular</b>		m	ft	4.0	13.1	6.0	19.7	8.0	26.2	10.0	32.8	12.0	39.4	14.0	45.9	16.0	52.5
Jeden bod zatížení	↓	kg	lbs	1491.0	3287.1	1083.3	2388.3	802.7	1769.6	632.1	1393.5	516.5	1138.7	432.3	953.1	367.8	810.9
prohyb	▲ — ▲	mm	inch	8.0	0.3	19.8	0.8	35.4	1.4	55.6	2.2	80.7	3.2	110.7	4.4	146.0	5.7
Dva body zatížení	↓ ↓	kg	lbs	946.0	2085.6	747.0	1646.9	602.0	1327.2	474.1	1045.2	387.4	854.1	324.2	714.7	275.8	608.0
prohyb	▲ — ▲	mm	inch	8.6	0.3	23.1	0.9	45.0	1.8	70.2	2.8	101.2	4.0	138.1	5.4	180.7	7.1
Tři body zatížení	↓ ↓ ↓	kg	lbs	713.0	1571.9	541.7	1194.2	401.3	884.7	346.0	762.8	258.2	569.2	216.1	476.4	183.9	405.4
prohyb	▲ — ▲	mm	inch	9.1	0.4	23.5	0.9	41.8	1.6	65.5	2.6	94.6	3.7	129.2	5.1	169.4	6.7
Čtyři body zatížení	↓ ↓ ↓ ↓	kg	lbs	586.0	1291.9	451.4	995.2	334.5	737.4	263.4	580.7	215.2	474.4	180.1	397.1	153.2	337.7
prohyb	▲ — ▲	mm	inch	9.5	0.4	24.9	1.0	44.3	1.7	69.3	2.7	99.9	3.9	136.3	5.4	178.5	7.0
Rovnoměrné zatížení	↓ ↓ ↓ ↓ ↓	kg	lbs	623.3	1374.1	361.1	796.1	200.7	442.5	126.4	278.7	86.1	189.8	61.8	136.2	46.0	101.4
prohyb	▲ — ▲	mm	inch	8.4	0.3	24.7	1.0	43.9	1.7	68.7	2.7	99.2	3.9	135.3	5.3	177.2	7.0

<b>M390 QUATRO heavy-duty</b>		m	ft	6.0	19.7	8.0	26.2	10.0	32.8	12.0	39.4	14.0	45.9	16.0	52.5	18.0	59.1
Jeden bod zatížení	↓	kg	lbs	1526.9	3366.2	1133.5	2498.9	894.7	1972.5	733.3	1616.6	616.1	1358.3	526.6	1161.0	455.4	1004.0
prohyb	▲ — ▲	mm	inch	19.8	0.8	35.4	1.4	55.6	2.2	80.5	3.2	110.3	4.3	145.3	5.7	185.6	7.3
Dva body zatížení	↓ ↓	kg	lbs	1054.0	2323.7	850.1	1874.1	671.0	1479.3	550.0	1212.5	462.1	1018.8	394.9	870.6	341.5	752.9
prohyb	▲ — ▲	mm	inch	23.2	0.9	44.9	1.8	70.2	2.8	101.3	4.0	138.1	5.4	180.7	7.1	229.2	9.0
Tři body zatížení	↓ ↓ ↓	kg	lbs	763.5	1683.2	566.7	1249.4	447.4	986.3	366.7	808.4	308.1	679.2	263.3	580.5	227.7	502.0
prohyb	▲ — ▲	mm	inch	23.5	0.9	41.8	1.6	65.5	2.6	94.5	3.7	129.1	5.1	169.2	6.7	215.0	8.5
Čtyři body zatížení	↓ ↓ ↓ ↓	kg	lbs	618.9	1364.4	472.3	1041.2	372.8	821.9	305.6	673.7	256.7	565.9	219.4	483.7	189.7	418.2
prohyb	▲ — ▲	mm	inch	24.2	1.0	44.3	1.7	69.3	2.7	99.9	3.9	136.3	5.4	178.4	7.0	226.4	8.9
Rovnoměrné zatížení	↓ ↓ ↓ ↓ ↓	kg	lbs	412.6	909.6	283.4	624.8	178.9	394.4	122.2	269.4	88.0	194.0	65.8	145.1	50.6	111.6
prohyb	▲ — ▲	mm	inch	20.1	0.8	43.9	1.7	68.8	2.7	99.2	3.9	135.3	5.3	177.1	7.0	224.8	8.9